

50MM BRASS COMBINATION PADLOCK

SET YOUR OWN COMBINATION

Step One

1. Set the dials to '0 0 0 0' which is the ex-factory pre-set combination.
2. Push down the shackle to open the padlock (figure 1).

Step Two

3. Insert the key firmly into the hole located on the side of the lock (figure 2). Turn the key 90° clockwise.
4. Set your own secret combination by turning the dials while the key is in position. Your new number must be positioned centrally across the base of the padlock, making sure each number clicks into position along the center line.
5. Memorize and record your secret number and remove the key by turning it anti-clockwise, taking care not to disturb the dials.

Step Three

6. Scramble the dials and then close the shackle.
7. The new secret combination is now set.

Step Four - To Open

8. Set the dials to your secret combination.
9. Push down on the shackle to open the padlock (figure 3).




Fig. 1



Fig. 2



Fig. 3



- A** = 51 mm
B = 41.7 mm
C = 26.8 mm
D = 8 mm
E = 25.1 mm
F = 25.3 mm

BBL Security Products guarantees this product and will replace it free of charge in the event:

1. The product fails due to defective material or manufacture.
2. The product has been maintained correctly.
3. The product has not been used for purposes other than for which it is designed.

MAINTENANCE: Clean and lubricate with lock graphite only